

Product Datasheet model skyguard NT 9175 260



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Product characteristics	• spectacles with all-round protection • complete eye protection against flying particles due to injection-moulded, soft TPU seal • reliable protection provided by its perfect fit: multi-level side arm lengths allow the wearer to adjust the spectacles to suit their own face shape • flexible soft component adapts to the wearer's face contours
Technical details Frame Material Colour Material Colour	Front piece PP blue TPU layer TPU grey

Manufacturer's ID code	Marking W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles)
Low-energy impact	F (45 m/s)
Conformity symbol	CE
Material	Side piece TPU+PC
Features	adjustable inclination
Colour	blue
Material	Temple PP
Features	adjustable to four different lengths
Colour	blue
Manufacturer's ID code	Marking W
Applicable EN norm	166
Low-energy impact	F (45m/s)
Conformity symbol	CE
Lens	
Material	PC
Thickness	2,1 mm
Coating	supravision excellence
Colour	clear
UV protection	UV 400

Filter	Marking
Manufacturer's ID code	2-1,2 (DIN EN 170)
Optical class	W
Low-energy impact	1
Surface resistance to fine particles	F (45 m/s)
Antifog	K
Conformity symbol	N
Factory symbol	CE
	
Miscellaneous	
Weight	42 g
Packing	5 spectacles
	160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170
PPE category	category II